



DYNAMIC MICROPHONE FOR VOCALS AND SPEECH: SENNHEISER XS 1

Wedemark, 14 September 2017 – Audio specialist Sennheiser is expanding its microphone portfolio with the wired XS 1 dynamic microphone. This rugged, entry-level mic brings Sennheiser quality to applications ranging from solo vocals to choir miking and speech. The cardioid XS 1 offers well-defined sound with an excellent presence in the mix. It is fitted with a lockable Mute switch and comes complete with a stand mount and leatherette pouch. The XS 1 will be available from November, and will be sold in Latin America, Asia (with the exception of Japan), Russia and the Middle East.

“The XS 1 is your ticket to great vocal sound,” says product manager Dennis Stegemerten. “No matter whether you are presenting, hosting an event, or singing – the XS 1 will be a reliable and versatile partner.”



The entry-level Sennheiser XS 1 is a cardioid, dynamic microphone that excels at vocals and speech

For music lovers and presenters

The XS 1 features balanced, full-bodied sound with a slight emphasis on the treble, which ensures that vocals will easily cut through high on-stage sound levels. Its cardioid pick-up pattern provides additional isolation from unwanted sound and great feedback rejection. The capsule is shock-mounted to minimise handling noise, while the mic's frequency response (55 to 16,000 Hz) filters out any structure-borne low-frequency noise.

In full control

The XS 1 provides great ease of use, with a silent Mute switch that puts users in full control of their sound transmission. Whenever the switch is not needed, it can be securely locked in the “On” position. The microphone has been designed to be rugged enough to take on a life of performing – with an all-metal body and a hardened sound inlet basket to protect its capsule.

The XS 1 cardioid dynamic microphone is delivered with a stand mount and a leatherette pouch for transport.

SENNHEISER



XS 1 Technical data

Transducer principle: dynamic

Pick-up pattern: cardioid

Frequency response 55 ... 16,000 Hz

Sensitivity (free field, no load, 1 kHz): 1.8 mV/Pa

Connector: XLR-3

Min. terminating impedance: 1 k Ω

Nominal impedance: approx. 300 Ω (at 1 kHz)

Dimensions: approx. \varnothing 48 mm x L 180 mm

Weight: approx. 330 g (0.73 lbs)

Temperature range: 0 °C ... +40 °C (+32 °F ... +104 °F)



About Sennheiser

Sennheiser is shaping the future of audio – a vision built on more than 70 years of innovation culture, which is deeply rooted within the family-owned company. Founded in 1945, Sennheiser is one of the world's leading manufacturers of headphones, microphones and wireless transmission systems. With 20 sales subsidiaries and long-established trading partners, the company is active in more than 50 countries and operates its own production facilities in Germany, Ireland and the USA. Sennheiser has around 2,800 employees throughout the world who share a passion for audio excellence. Since 2013, Sennheiser has been managed by Daniel Sennheiser and Dr. Andreas Sennheiser, the third generation of the family to run the company. In 2016, the Sennheiser Group had sales totalling €658.4 million. www.sennheiser.com

Local Contact

Global Contact

[Stephanie Schmidt](#)

stephanie.schmidt@sennheiser.com

T +49 (5130) 600 – 1275