



L 300 10-10

10 + 10 bay charger for HDI 830 and BA 300



FEATURES

- 10 plus 10 bay parallel charging unit for HDI 830 receivers and BA 300 batteries
- LED charging controls
- Full charge in 3 hours
- Mains supply with 4 country adaptors

The L 300 10-10 charger quickly charges up to 10 receivers and up to 10 BA 300 rechargeable batteries in parallel. It is especially easy to use since the receivers can be inserted into the charging compartments either way round. Compatible are RI 830/RI 830 S, HDI 830, RI 900, RR 840/RR 840 S receivers and BA 300 rechargeable batteries.

SPECIFICATIONS

L 300 10-10 charger	
Charging time	approx. 3h
Charging current per charging compartment	approx. 70 mA
Current consumption	max. 2 A
Voltage	6 V
Weight	approx. 530 g
Dimensions	400 x 130 x 50 mm
Ambient temperature	0 °C - +40 °C

NT 6 mains unit	
Nominal input voltage	100 - 240 V ~
Nominal input current	max. 0.5 A
Mains frequency	50 - 60 Hz
Nominal output voltage	6 V
Nominal output current	max. 2.5 A
Operating temperature	0 °C - +45 °C
Storage temperature	25 °C - +75 °C
Weight	145 g
Dimensions	71.7 x 50 x 33.2 mm

ARTICLE INFORMATION

L 300 10-10	Art. no. 502710
-------------	-----------------

ACCESSORIES

NT 6 mains unit	Art. no. 570692
4 country adaptors (EU/UK/US/AU)	Art. no. 578895

ARCHITECT'S SPECIFICATION

A mains driven charger shall supply 10 charging compartments for rechargeable batteries plus 10 charging compartments for stetho or bodypack receivers. Both types can be charged at the same time. Mounting plates are available for fixed installation on an even surface. A mains unit with country adaptors for EU, UK, US and AU is included in delivery. The charger shall work with Sennheiser BA 300 batteries as well as RI 830/RI 830 S, HDI 830, RI 900, RR 840/RR 840 S receivers.

DIMENSIONS

